

Fujitsu recommends Windows® 7.

Data Sheet

Fujitsu CELSIUS W520 Workstation

Performance That Boosts Your Productivity

If you need a powerful entry-level workstation, Fujitsu's CELSIUS W520 is the ideal choice. Comprehensive ISV certifications ensure your professional applications run smoothly. Your workplace is silent and user-friendly thanks to best-in-class noise emissions. Plus, the cold plug access at the front of the workstation lets you expand your storage capacity or change drives for enhanced working flexibility.

Powerful workstation

Get more done in less time

- The fastest available processors, graphics cards and hard disk drives for entry-level 3D/CAD or DCC applications

Quality

Highest quality and reliability for continuous productivity

- Designed and manufactured in Germany

Upgradeability

Minimum downtime in the event of rapid component upgrades

- Screw less access system design

Leading workstation application certification




Maximum compatibility and performance with customer-preferred applications

- Full support for ISV applications and easy integration into existing IT environments

Easy and rapid change of hard disk drives

Quick upgrades and changes of hard disk drives

- Cold plug access at front



Components

Processor	Intel® Core™ i3-3220 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2500)
	Intel® Core™ i3-2130 processor (2 Cores / 4 Threads, 3.40 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Core™ i3-2120 processor (2 Cores / 4 Threads, 3.30 GHz, 3 MB, Intel® HD Graphics 2000)
	Intel® Xeon® processor E3-1290v2 (4 Cores / 8 Threads, 3.70 GHz, up to 4.1 GHz, 8 MB)
	Intel® Xeon® processor E3-1280v2 (4 Cores / 8 Threads, 3.60 GHz, up to 4.0 GHz, 8 MB)
	Intel® Xeon® processor E3-1275v2 (4 Cores / 8 Threads, 3.50 GHz, up to 3.9 GHz, 8 MB, Intel® HD Graphics P4000)
	Intel® Xeon® processor E3-1270v2 (4 Cores / 8 Threads, 3.50 GHz, up to 3.9 GHz, 8 MB)
	Intel® Xeon® processor E3-1245v2 (4 Cores / 8 Threads, 3.40 GHz, up to 3.8 GHz, 8 MB, Intel® HD Graphics P4000)
	Intel® Xeon® processor E3-1240v2 (4 Cores / 8 Threads, 3.40 GHz, up to 3.8 GHz, 8 MB)
	Intel® Xeon® processor E3-1230v2 (4 Cores / 8 Threads, 3.30 GHz, up to 3.7 GHz, 8 MB)
	Intel® Xeon® processor E3-1225v2 (4 Cores / 4 Threads, 3.20 GHz, up to 3.6 GHz, 8 MB, Intel® HD Graphics P4000)
	Intel® Xeon® processor E3-1220v2 (4 Cores / 4 Threads, 3.10 GHz, up to 3.5 GHz, 8 MB)
	Intel® vPro™ with all Intel® Xeon® processors
Operating systems	
Operating system	Windows® 7 Professional 64-bit
	Windows® 7 Professional 32-bit
	Windows® 7 Home Premium 64-bit
Operating system compatible	
Windows® XP Linux	
Operating system notes	
Red Hat® certification pending Novell® certification pending For some configurations third party drivers are currently not available or configuration restrictions may apply. Limited Windows® XP support. Microsoft discontinued Windows® XP certification on system level, basic drivers via http://support.ts.fujitsu.com	
Memory modules	
2 GB (1 module(s) 2 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM	
2 GB (1 module(s) 2 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM	
4 GB (1 module(s) 4 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM	
4 GB (1 module(s) 4 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM	
8 GB (1 module(s) 8 GB) DDR3, unbuffered, ECC, 1600 MHz, PC3-12800, DIMM	
8 GB (1 module(s) 8 GB) DDR3, unbuffered, non-ECC, 1600 MHz, PC3-12800, DIMM	
Graphics add on cards (optional)	
Ultra-high-end 3D: NVIDIA® Quadro® K5000, 4 GB, 352 cores, PCIe x16, Dual Link DVI-I, DVI-D, 2x DisplayPort	
Ultra-high-end 3D: NVIDIA® Quadro® 5000, 2.5 GB, 352 cores, PCIe x16, Dual Link DVI-I, 2x DisplayPort	
High-end 3D: AMD FirePro™ W7000, 4 GB, 1140 stream processors, PCIe x16, 4 x DisplayPort	
High-end 3D: AMD FirePro™ V7900, 2 GB, 1140 stream processors, PCIe x16, 4 x DisplayPort	
High-end 3D: NVIDIA® Quadro® 4000, 2 GB, 256 cores, PCIe x16, Dual Link DVI-I, 2x DisplayPort	
Midrange 3D: NVIDIA® Quadro® 2000D, 1 GB, 192 cores, PCIe x16, 2x Dual Link DVI-I	
Midrange 3D: NVIDIA® Quadro® 2000, 1 GB, 192 cores, PCIe x16, Dual Link DVI-I, 2x DisplayPort	
Midrange 3D: AMD FirePro™ W5000, 2 GB, 800 stream processors, PCIe x16, Dual Link DVI-I, 2x DisplayPort	
Midrange 3D: AMD FirePro™ V5900, 2 GB, 800 stream processors, PCIe x16, Dual Link DVI-I, 2x DisplayPort	
Entry 3D: AMD FirePro™ V4900, 1 GB, 480 stream processors, PCIe x16, Dual Link DVI-I, 2x DisplayPort	
Entry 3D: NVIDIA® Quadro® 600, 1 GB, 96 cores, PCIe x16, Dual Link DVI-I, DisplayPort	
Entry 3D: AMD FirePro™ V3900, 1 GB, 480 stream processors, PCIe x16, Dual Link DVI-I, DisplayPort	
Entry 3D: NVIDIA® Quadro® 410, 512 MB, 192 cores, PCIe x16, 1x DVI-I, DisplayPort	
Professional 2D: NVIDIA® Quadro® NVS 450, 512 MB, 2 x 8 cores, PCIe x16, 4 x DisplayPort	
Professional 2D: NVIDIA® Quadro® NVS 300, 512 MB, 16 cores, PCIe Gen2 x16, 2x DVI/VGA	
Remote Graphics: CELSIUS RemoteAccess Card, PCIe x1, 2x DVI-I, PCoIP	
Notes	
NVIDIA® Quadro® 5000, NVIDIA® Quadro® 4000 and ATI FirePro™ V7900 require CELSIUS W520power.	

Hard disk drives (internal)	SSD SATA III, 512 GB, 2.5-inch	
	SSD SATA III, 256 GB, 2.5-inch	
	SSD SATA III, 128 GB, 2.5-inch, SED	
	SSD SATA III, 128 GB, 2.5-inch	
	SSD SATA III, 64 GB, 2.5-inch	
	SSD SATA, 256 GB, 2.5-inch	
	SSD SATA, 128 GB, 2.5-inch, FDE	
	SSD SATA, 128 GB, 2.5-inch	
	HDD SATA III, 10000 rpm, 600 GB, 3.5-inch	
	HDD SATA III, 10000 rpm, 600 GB, 2.5-inch	
	HDD SATA III, 10000 rpm, 300 GB, 2.5-inch	
	HDD SATA III, 7200 rpm, 2000 GB, 3.5-inch	
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch, business critical	
	HDD SATA III, 7200 rpm, 1000 GB, 3.5-inch	
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch, business critical	
	HDD SATA III, 7200 rpm, 500 GB, 3.5-inch	
	HDD SATA III, 7200 rpm, 250 GB, 3.5-inch	
	HDD SATA II, 7200 rpm, 2000 GB, 3.5-inch, business critical	
	HDD SATA, 160 GB, 2.5-inch	
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. 24/7 ready (business critical HDDS required) Up to 18 GB of HDD space is reserved for system recovery	
Drives (optional)	BD Triple Writer SATA slim (tray)	
	Blu-ray Disc™ Triple Writer	
	DVD-ROM	
	DVD Super Multi	
	MultiCard Reader 20in1, USB 2.0, 3.5-Inch	
	MultiCard Reader 24in1 USB 2.0 3.5"	
Interface add on cards/components (optional)	WLAN III, 802.11g/Draft-n (Windows only)	
	Parallel Interface	
	Gigabit Ethernet PCIe x1, DS	
	eSATA Interface	
	Dual serial card PCIe x1, powered	
	Dual serial card PCIe x1	
Base unit	CELSIUS W520	CELSIUS W520power
Mainboard		
Mainboard type	D3167	
Formfactor	ATX	
Chipset	Intel® C216	
Processor socket	LGA 1155	
Processor quantity maximum	1	
Memory slots	4 DIMM (DDR3) ECC/non-ECC	
Supported capacity RAM (max.)	32 GB	
Memory frequency	1600 MHz	
Memory notes	Dual channel support. For dual channel performance, a minimum of 2 memory modules have to be ordered. Capacity per channel has to be the same.	
LAN	10/100/1000 MBit/s Intel® 82579 LM	

Mainboard

BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio codec	Conexant CX20642
Audio features	Internal speaker supports audio playback, High Definition audio, 5.1 surround sound

I/O controller on board

Serial ATA total	6
thereof SATA III	2
thereof eSATA	2 (optional)
Controller functions	Serial ATA II (3 Gbit) Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10 (Windows XP not supported) Intel® Smart Response Technology (depending on CPU)
SATA RAID support	0, 1, 10, 5

Interfaces

Audio: in (rear)	2
Audio: out (rear)	1
Audio: in	1
Audio: out	1
Internal speakers	1
USB 2.0 total	10
USB front	2x 2.0/ 2x 3.0
USB rear	6x 2.0 / 2x 3.0
USB internal	1 + 1
VGA	1 (depends on processor, via DVI to VGA adapter)
DisplayPort	1
DVI	1 (depends on processor)
Serial (RS-232)	1 (9pin, 16 byte FIFO, 16550 compatible)
Mouse / Keyboard (PS/2)	2
Ethernet (RJ-45)	1
Parallel	1, optional (25pin with EPP and ECP)
eSATA	1 (optional)
Interface Module notes	Anytime USB charge functionality

Drive bays

Drive bays total	8
3.5-inch internal bays	4
3.5-inch external bays	2
5.25-inch external bays	2

Slots

PCI-Express 2.0 x16	1 x (312 mm /) Full height
PCI-Express 2.0 x4 (mech. x16)	1 x (210 mm /) Full height
PCI-Express x1	3 x (312mm (2x) / 170 mm (1x) mm /) Full height
PCI (32-bit / 33 MHz)	2 x (312 mm /) Full height

Graphics on board

Shared video memory	up to 1759 MB
---------------------	---------------

Graphics on board

TFT resolution (VGA)	1024 x 768 pixel
	1280 x 1024 pixel
	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1600 x 1200 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
TFT resolution (DVI)	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
TFT resolution (DisplayPort)	1360 x 768 pixel
	1440 x 900 pixel
	1600 x 900 pixel
	1680 x 1050 pixel
	1920 x 1080 pixel
	1920 x 1200 pixel
	2560 x 1440 pixel
	2560 x 1600 pixel
Graphics features	Dual display support
	DirectX® 10.1 or DirectX® 11 (depending on CPU)
	HDCP support
	Open GL® 3.1 (depending on CPU)
	Open CL™ 1.1 (depending on CPU)
Graphics notes	For multi monitoring mode, graphics card and integrated graphics run in parallel (Microsoft® Windows 7® only)
	Tested resolutions, depending on display type additional resolutions and frequencies possible
	Shared memory depending on main memory size and operating system
	Resolution (color depth up to 32 Bit/pixel)
	For TFT we recommend using 60Hz

Electrical values

Power efficiency note	power supply efficiency (at 230V; 20% / 50% / 100% load) : 87% / 90% / 87%	
Rated voltage range	100 V - 240 V	
Rated frequency range	50 Hz - 60 Hz	
Operating voltage range	90 V - 264 V	
Operating line frequency range	47 Hz - 63 Hz	
Max. output of single power supply	300 W (CELSIUS W520); 500 W (CELSIUS W520power)	
Power factor correction/active power	active	

Noise for standard configuration (HDD, ODD)

Noise Operation mode 4: High load	18 dB(A)	18 dB(A)
Noise Operation mode 5: Office applications	18 dB(A)	18 dB(A)
Idle mode	tbd	tbd
Office mode	tbd dB(A)	tbd dB(A)

Dimensions / Weight / Environmental

Dimensions (W x D x H)	186 x 481 x 430 mm
Operating position	Vertical / horizontal
Weight	approx. 16 kg
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35°C
Operating relative humidity	5 - 85 % (relative humidity)

Compliance

Product	CELSIUS W520power
Model	MTB-D3167
Germany	TÜV GS
Europe	CE
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® in progress EPEAT® in progress (dedicated regions)
Compliance notes	Energy Star compliance may vary depending on actual configuration
Compliance link	https://sp.ts.fujitsu.com/sites/certificates/

Security

System protection	Kensington Lock support Eye for padlock Seal option Intrusion switch Optional: Integrated cabinet lock
Audit proof protection	EraseDisk Boot sector virus protection Write protect option for the Flash EPROM Embedded security (TPM 1.2) Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces
Access protection	User and supervisor BIOS password Hard disk password Optional: Access protection via external SmartCard reader Optional: Access protection via internal SmartCard reader Optional: SmartCase Logon+

Additional Software

Additional software (preinstalled)	Nero Essentials S (burning software) Fujitsu Recovery (Hard Disk Based Recovery) Norton Internet Security (incl. Firewall) 60 days version Microsoft® Office Starter: reduced-functionality Word and Excel® only, with advertising. No PowerPoint® or Outlook®. Buy Office 2010 to use the full-featured software.
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™, only with Blu-ray Disc™ drive / Blu-ray playback is not supported under Windows XP if the system runs on Intel onboard graphics) Nero 10 Essentials XL

Miscellaneous

	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime	Keyboard on (Special Fujitsu keyboard required) Thermal management Extended lifetime
--	--	--

Manageability

Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) iAMT 8.0 (depending on CPU)
Manageability software	DeskView 10.x client management including:

Manageability

DeskView components	On/Offline remote client management Detailed system inventory management and reports BIOS Management Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)
Manageability link	http://ts.fujitsu.com/manageability http://www.altiris.com/fujitsu http://ts.fujitsu.com/solutions/it_infrastructure_solutions/manageability/featurefinder.html

Input device / components

	Optical USB tilt wheel mouse
Input devices (optional)	Optical USB/PS2 tilt wheel mouse KBPC PX ECO Mouse M440 ECO Space Explorer USB Keyboard

Warranty

Standard Warranty	3 years (depending on country)
Service level	On-site Service (depending on country)
Maintenance and Support Services - the perfect extension	
Recommended Service	5x9, Response Time: Next Business Day
Service Weblink	http://ts.fujitsu.com/Supportservice

More information

Fujitsu OPTIMIZATION Services

In addition to Fujitsu CELSIUS W520, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/services/computing/

Software

www.fujitsu.com/software/

More information

Learn more about Fujitsu CELSIUS W520, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/fts/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment/>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

For further information see www.fujitsu.com/terms

Copyright © Fujitsu Technology Solutions

Disclaimer

Technical data are subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

FUJITSU Technology Solutions
Website: www.fujitsu.com/fts
2012-10-02 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
Copyright © Fujitsu Technology Solutions